


**SPECIFICATIONS**

**TEG126-60**

Specially designed for high temperature application by EVERREDtronics, the thermoelectric generator can withstand temperature as high as 330°C (626 F ) heat source continuously and up to 400°C (752 F ) intermittently and thus are widely used for industrial waste heat recovery, automobile exhaust gas heat reclamation or various stove heat recycle.


Under 270 Celsius Degree gradient between hot side and cold side, the module can deliver as high as 19.3W power.

**Specification of the Module**




Hot Side Temperature (°C)	300
Cold Side Temperature (°C)	30
Open Circuit Voltage (V)	8.4
Matched Load Resistance (ohms)	0.9
Matched load output voltage (V)	4.2
Matched load output current (A)	4.6
Matched load output power (W)	19.3
Heat flow across the module(W)	≈ 386
Heat flow density(Wcm <sup>-2</sup> )	≈ 12.3
AC Resistance(ohms) Measured under 27°C at 1000Hz	0.25~0.45

**Geometric Characteristics** Dimensions in millimeter



Hot Side Attached to Heat source




Cold Side Attached to Heat Sink for Heat Dissipation


愉進電子科技有限公司  
**EVERREDTRONICS LIMITED**

上海市宝山区菊联路 89 号 201907  
 No 89 Julian Road, Baoshan, Shanghai 201907 China.  
 Tel:+86-21-6049 5160 Fax:+86-21-6531 1544  
 URL: [www.everredtronics.com](http://www.everredtronics.com) E-mail: [sales@everredtronics.com](mailto:sales@everredtronics.com)


**SPECIFICATIONS**




The chart for open circuit voltage Vs  $T_h$  under various  $T_c$




The chart for matched load resistance Vs  $T_h$  under various  $T_c$




The chart for matched load voltage Vs  $T_h$  under various  $T_c$



The chart for matched load current Vs  $T_h$  under various  $T_c$



The chart for matched load output power Vs  $T_h$  under various  $T_c$



The chart for output voltage and output power Vs output current under  $T_h=300^\circ\text{C}$  and  $T_c=30^\circ\text{C}$